

FVG series vacuum filters are especially recommended for fine filtration. Their light weight allows easy on-board installation.

### Mini-filters

Models	Vacuum pumps
FVG 3	GVP 10 - VR 07 - VR 09
FVG 5	GVP 12 and 14
FVG 6	GVP 20

### Characteristics

Models	A	B	C	E	F	G	D1	D2
FVG 3	8	20.5	33.8	55	50	18	G1/8"-F	G1/8"-F
FVG 5	12.5	25	42	65	50	23	G1/4"-F	G1/4"-F
FVG 6	15	30	47	70	60	23	G3/8"-F	G3/8"-F




Note: all dimensions are shown in (mm)

### Specifications



Operating pressure	-1 to 5 bar
Temperature	0 to 60 °C
Filtration (μ)	FVG 3-5-6 : 40
Weight (g)	FVG 3/5/6: 70/138.5/220
Material	Body : POM Hood : Polycarbonate Seal : Nitrile (NBR) Screws / large washers : Polyethylene and plated steel Filter : Porex

### Accessories

Replacement cartridges: interchangeable filtration element.  
Add E to the filter model reference to order the replacement cartridge.



(1) D1 (input)  
(2) DE (Output)



Filtration angle 300°



For all orders, please specify:  
Model + Type + Filter or Cartridge  
e.g.: FVG5

1: Model	2: Type	3: Filter or Cartridge
FVG	3 FVG 3 5 FVG 5 6 FVG 6	- Filter E Cartridge