

Foam Rings



The foam ring is designed for gripping products with an uneven or ridged surface, e.g.,

- Sawn wood, sheet metal, flat surfaces with bumps or hollows.
- All granular surfaces to which suction cups cannot adhere correctly and therefore cannot be airtight.

Industry-specific applications







Types of use



Materials

NBR Nitrile

SI Non Food-grade silicone

SIF

Food-grade silicone FDA Standard

Operating Characteristics of the Materials

■ Nitrile (NBR - Black)

5 or 10mm thick, depending on the diameters of the suction cups. Good resistance to oil.

The nitrile foam strip can only be bonded to nitrile suction cups.

■ Silicone (SI - White non Food-grade silicone, SIF - White Food-grade silicone FDA Standard)

2 or 5 mm thick, depending on the diameters of the suction cups.

Heat-resistant up to 200°C, does not leave marks on products handled.

Do not use the silicone foam strip for gripping products before painting or lacquering.


The silicone foam strip can only be bonded onto silicone suction cups (bonding is guaranteed if it is carried out in the factory).

■ Mounting

The foam rings are mounted by bonding. In all cases, this should be performed in our factory as we have the adhesives adapted to the materials. It is essential that bonding of silicone be carried out in the COVAL factory.

| NBR | | | | | | SI / SIF | | | | | |
|----------|----|-----|----|------------------|-------------|----------------|----|-----|---|------------------|-------------|
| Part Nr. | ØA | ØA1 | C | f ⁽¹⁾ | <u></u> (g) | Part Nr. | ØA | ØA1 | С | f ⁽¹⁾ | <u></u> (g) |
| VSBM32 | 32 | 22 | 5 | 2.5 | 0.3 | VSBM20SI / SIF | 20 | 10 | 2 | 1.0 | 0.2 |
| VSBM42 | 42 | 28 | 5 | 2.5 | 0.7 | VSBM25SI / SIF | 25 | 13 | 2 | 1.0 | 0.4 |
| VSBM53 | 53 | 33 | 10 | 5.0 | 2.7 | VSBM32SI / SIF | 32 | 19 | 2 | 1.0 | 0.5 |
| VSBM62 | 62 | 42 | 10 | 5.0 | 2.8 | VSBM42SI / SIF | 42 | 20 | 5 | 2.5 | 2.2 |
| VSBM78 | 78 | 58 | 10 | 5.0 | 3.7 | VSBM53SI / SIF | 53 | 33 | 5 | 2.5 | 2.8 |
| VSBM88 | 88 | 68 | 10 | 5.0 | 4.6 | VSBM62SI / SIF | 62 | 42 | 5 | 2.5 | 3.4 |
| | | | · | | | VSBM78SI / SIF | 78 | 54 | 5 | 2.5 | 5.2 |
| | | | | | | VSBM88SI / SIF | 88 | 64 | 5 | 2.5 | 6.4 |

Note: Suction cups with bellows are preferable when foam rings are required, as the slope of the lips is better suited to this type of grip. Please consult us for other models based on quantities.





Please specify the part n°. e.g. VSBM32SI See part n° table above The values represent the average characteristics of our products.

(1) f = Deflection of the suction cup.

Note: All dimensions are in mm.

